

Impulse Response Measurements in the 1850-1990 MHz Band in Large Outdoor Cells

**J.A. Wepman
J.R. Hoffman
L.H. Loew**



**U.S. DEPARTMENT OF COMMERCE
Ronald H. Brown, Secretary**

Larry Irving, Assistant Secretary
for Communications and Information

June 1994

Product Disclaimer

Certain commercial equipment, instruments, or materials are identified in this paper to specify adequately the technical aspects of the reported results. In no case does such identification imply recommendation or endorsement by the National Telecommunications and Information Administration, nor does it imply that the material or equipment identified is necessarily the best available for the purpose.

CONTENTS

	Page
FIGURES	vi
TABLES	viii
ABSTRACT	1
1. INTRODUCTION	1
2. MEASUREMENT SYSTEM	3
2.1 Transmitter	3
2.2 Receiver	3
3. MEASUREMENT PROCEDURE	9
4. MEASUREMENT LOCATIONS	13
5. DATA ANALYSIS METHODS AND RESULTS	17
5.1 Delay Statistics	18
5.2 Effects of Spatial Diversity	26
5.3 Multipath Power Statistics	28
5.4 Number of Paths, Path Arrival Time, and Path Power Statistics	33
5.5 Correlation Bandwidth	42
6. SUMMARY AND CONCLUSIONS	47
7. REFERENCES	49

FIGURES

	Page
Figure 2.1. Photograph of the measurement system transmitter van	4
Figure 2.2. Photograph of the measurement system receiver van	5
Figure 2.3. Block diagram of the measurement system transmitter	6
Figure 2.4. Block diagram of the measurement system receiver	7
Figure 3.1. Example calibration power delay profile	10
Figure 4.1. Measurement routes in the flat rural cell	14
Figure 4.2. Measurement routes in the hilly rural cell	15
Figure 4.3. Measurement routes in the urban high-rise cell	16
Figure 5.1. Histograms of maximum delay (a), mean delay (b), and RMS delay spread (c) for the flat rural cell using a threshold 20 dB below the peak in each APDP	20
Figure 5.2. Histograms of maximum delay (a), mean delay (b), and RMS delay spread (c) for the hilly rural cell using a threshold 20 dB below the peak in each APDP	21
Figure 5.3. Histograms of maximum delay (a), mean delay (b), and RMS delay spread (c) for the urban high-rise cell using a threshold 20 dB below the peak in each APDP	22
Figure 5.4. Cumulative distributions of maximum delay (a), mean delay (b), and RMS delay spread (c) for the flat rural cell using a threshold 20 dB below the peak in each APDP	23
Figure 5.5. Cumulative distributions of maximum delay (a), mean delay (b), and RMS delay spread (c) for the hilly rural cell using a threshold 20 dB below the peak in each APDP	24
Figure 5.6. Cumulative distributions of maximum delay (a), mean delay (b), and RMS delay spread (c) for the urban high-rise cell using a threshold 20 dB below the peak in each APDP	25
Figure 5.7. Effects of spatial diversity in the flat rural (a), hilly rural (b), and urban high-rise (c) cells	27

FIGURES (cont'd)

	Page
Figure 5.8. Average and standard deviation of power (a), peak power (b), and threshold statistics (c) for the flat rural cell	30
Figure 5.9. Average and standard deviation of power (a), peak power (b), and threshold statistics (c) for the hilly rural cell	31
Figure 5.10. Average and standard deviation of power (a), peak power (b), and threshold statistics (c) for the urban high-rise cell	32
Figure 5.11. Cumulative distributions of the number of significant paths for different thresholds for the flat rural (a), hilly rural (b), and urban high-rise (c) cells	34
Figure 5.12. Histograms (a-b) and cumulative distributions (c) of correlation bandwidth for the flat rural cell	44
Figure 5.13. Histograms (a-b) and cumulative distributions (c) of correlation bandwidth for the hilly rural cell	45
Figure 5.14. Histograms (a-b) and cumulative distributions (c) of correlation bandwidth for the urban high-rise cell	46

TABLES

Page

Table 5.1. Mean (μ) and Standard Deviation (σ) of Path Arrival Time (in μs) and Path Power (in dB) Using a -20 dB Threshold for Each Individual Path for APDPs Having a Total of n Paths in the Flat Rural Cell	36
Table 5.2. Mean (μ) and Standard Deviation (σ) of Path Arrival Time (in μs) and Path Power (in dB) Using a -20 dB Threshold for Each Individual Path for APDPs Having a Total of n Paths in the Hilly Rural Cell	37
Table 5.3. Mean (μ) and Standard Deviation (σ) of Path Arrival Time (in μs) and Path Power (in dB) Using a -20 dB Threshold for Each Individual Path for APDPs Having a Total of n Paths in the Urban High-Rise Cell	38
Table 5.4. Mean (μ) and Standard Deviation (σ) of Path Arrival Time (in μs) and Path Power (in dB) Using a -10 dB Threshold for Each Individual Path for APDPs Having a Total of n Paths in the Flat Rural Cell	39
Table 5.5. Mean (μ) and Standard Deviation (σ) of Path Arrival Time (in μs) and Path Power (in dB) Using a -10 dB Threshold for Each Individual Path for APDPs Having a Total of n Paths in the Hilly Rural Cell	40
Table 5.6. Mean (μ) and Standard Deviation (σ) of Path Arrival Time (in μs) and Path Power (in dB) Using a -10 dB Threshold for Each Individual Path for APDPs Having a Total of n Paths in the Urban High-Rise Cell	41